

Vertical Blind Installation Instructions


Top Fixing Brackets

Fix brackets to ceiling or lintel with holes drilled on a line at least 3" (75mm) from the wall or window frame for blinds with 5" (127mm) louvres or 2 1/8" (55mm) for blinds with 3 1/2" (89mm) louvres. End brackets should be about 1 1/2" (40mm) from the ends of the track. Any remaining brackets should be spaced evenly between these two brackets."



Face Fixing Brackets

Fix brackets to wall or window frame as closely as possible to the ceiling or lintel with same spacing as recommended for the top fixing brackets.



Fitting the Louvres

Turn hooks so that the slots are 90o to the track. Hang the louvres, keeping all seams one way. Your blind is now ready to operate.

How to clean your Vertical Blinds :

Your louvres may have been made with a special washable fabric. If this is so follow the cleaning instructions carefully that have been supplied with the louvres. However, if you are in any doubt please proceed as follows:-

1. Remove the louvres and wipe with a clean cloth that has been dampened with a solution of mild detergent.
2. Wipe with a clean, damp cloth.
3. Place louvres between clean, dry cloths and iron lengthwise using an iron set to 'cool'.
4. Re-hang the louvres while still damp.

Important : To minimise shrinkage during the cleaning process, fabrics must not be allowed to become more than slightly damp.